

MODEL	PR-127	PR-147	PR-167	PR-187	PR-207	PR-227	PR-247	PR-128-1	PR-128-2	PR-168	PR-208	PR-228	PR-248
APPROXIMATE # OF SNOWMOBILES	2	2	2	2-3	3	4	4	2	2	3	3-4	4	4
APPROXIMATE # OF ATVS	2	2	2	2-3	2-3	3	3-4	2	2	3-4	4	4	4
APPROXIMATE # OF UTVS	1	1	1	1	1-2	2	2	1	1	1	1-2	2	2
BED WIDTH (IN.)	80.5	80.5	80.5	80.5	80.5	80.5	80.5	98	98	98	98	98	98
BED LENGTH (FT.)	12	14	16	18	20	22	24	12	12	16	20	22	24
BED LENGTH INCLUDING V-NOSE (FT.)	17	19	21	23	25	27	29	17	17	21	25	27	29
OVERALL LENGTH (FT.)	20.5	22.5	24.5	26.5	28.5	30.5	32.5	20	20	24	28	30	32
REAR DOOR 6' BOX (IN.) width x height	76 x 69	76 x 69	76 x 69	76 x 69	76 x 69	76 x 69	76 x 69	92 x 69	92 x 69	92 x 69	92 x 69	92 x 69	92 x 69
FRONT DOOR 6' BOX (IN.) width x height	62 x 65	62 x 65	62 x 65	62 x 65	62 x 65	62 x 65	62 x 65	62 x 65	62 x 65	62 x 65	62 x 65	62 x 65	62 x 65
REAR DOOR 6'6" BOX (IN.) width x height	76 x 75	76 x 75	76 x 75	76 x 75	76 x 75	76 x 75	76 x 75	92 x 75	92 x 75	92 x 75	92 x 75	92 x 75	92 x 75
FRONT DOOR 6'6" BOX (IN.) width x height	62 x 71	62 x 71	62 x 71	62 x 71	62 x 71	62 x 71	62 x 71	62 x 71	62 x 71	62 x 71	62 x 71	62 x 71	62 x 71
REAR DOOR 7' BOX (IN.) width x height	76 x 81	76 x 81	76 x 81	76 x 81	76 x 81	76 x 81	76 x 81	92 x 81	92 x 81	92 x 81	92 x 81	92 x 81	92 x 81

MODEL	PR-127	PR-147	PR-167	PR-187	PR-207	PR-227	PR-247	PR-128-1	PR-128-2	PR-168	PR-208	PR-228	PR-248
FRONT DOOR 7' BOX (IN.) width x height	62 x 77	62 x 77	62 x 77	62 x 77	62 x 77	62 x 77	62 x 77	62 x 77	62 x 77	62 x 77	62 x 77	62 x 77	62 x 77
REAR DOOR 7'6" BOX (IN.) width x height	76 x 87	76 x 87	76 x 87	76 x 87	76 x 87	76 x 87	76 x 87	92 x 87	92 x 87	92 x 87	92 x 87	92 x 87	92 x 87
FRONT DOOR 7'6" BOX (IN.) width x height	62 x 83	62 x 83	62 x 83	62 x 83	62 x 83	62 x 83	62 x 83	62 x 83	62 x 83	62 x 83	62 x 83	62 x 83	62 x 83
CARRYING CAPACITY (LB.)	3450	3350	3250	4150	3925	3700	3475	1605	3400	3100	3650	3525	3400
GVWR (LB.)	5000	5000	5000	6000	6000	6000	6000	2995	5000	5000	6000	6000	6000
TRAILER WEIGHT (LB.)	1550	1650	1750	1850	2075	2300	2525	1390	1600	1900	2350	2475	2600
NUMBER OF AXLES	2	2	2	2	2	2	2	1	2	2	2	2	2
HITCH HEIGHT (IN.)* from top of ball	18	18	18	18	18	18	18	25	25	25	25	25	25
STANDARD TIRES	ST205/75 R14C	ST205/75 R14C	ST205/75 R14C	ST205/75 R14C	ST205/75 R14C	ST205/75 R14C	ST205/75 R14C	175/80 R13D	175/80 R13D	175/80 R13D	175/80 R13D	175/80 R13D	175/80 R13D
TIRE UPGRADE OPTIONS WITH ALUMINUM RIMS	ST205/75 R14C	ST205/75 R14C	ST205/75 R14C	ST205/75 R14C	ST205/75 R14C	ST205/75 R14C	ST205/75 R14C	165/75 R13D	165/75 R13D	165/75 R13D	165/75 R13D	165/75 R13D	165/75 R13D

*Hitch height of ball will increase 4" if equipped with surge disc brakes. Measure your vehicles for actual needed model size. Recommended tongue weight for enclosed trailers is 7-10% of GVWR. Please note: It is the responsibility of the purchaser to adhere to the brake laws regarding trailers. For full information on trailering laws, contact the appropriate Motor Vehicle Department. Brake options will change the overall length of trailer. Contact your local Triton dealer for order lead times. All trailers ordered without brakes will have a GVWR of 2995#. Specifications, and accessories can change without notice.