



IDEAL CARGO

IDEALTRAILER.COM

Stand Up to Time!



AVANTAGES



A TRAILER THAT STAYS **AHEAD OF THE COMPETITION**



The Avantages model, supported by Duracore technology, offers the best value for the entire range of Ideal Cargo products. We use quality materials and diverse manufacturing processes to develop a more economical trailer suiting your every need.

Characteristics:

- Leaf axle (optional torsion)
- Fully hot-dipped galvanized structure
- Galvanized steel wheels
- High-quality radial tires
- Zinc steel hardware (optional aluminum)
- Lights with integrated switches
- Duracore technology unique to Ideal Cargo
- Pre-painted exterior aluminum sheet, screwed and sealed against water infiltration (optional glued)
- One-piece aluminum roof
- Angled 3-inch-long V-head
- Decorative anodized aluminum front head
- Thermal barrier to prevent corrosion
- Waterproofed, sealed floor made of 5/8" plywood
- Trailer protected by a marking system
- LED exterior lights
- 3/8" plywood walls
- Chromed center cap

FIND OUT MORE ON THIS MODEL BY CONSULTING OUR "TRAILERS" SECTION AT WWW.IDEALTRAILER.COM



CORROSION OF THE STRUCTURE



BONDED ALUMINUM EXTERIOR



STRUCTURAL FAILURE



WATER INFILTRATION THROUGH THE ROOF



ALUMINUM PUNCTURE

TECHNICAL SPECIFICATIONS

	AV5x8SA	AV6x12TA2	AV7x14TA2	AV8,5x20TA2
Overall length (approx.)	13' - 0"	18' - 0"	20' - 0"	26' - 0"
Overall width	6' - 10"	7' - 10"	8' - 6"	8' - 6"
Overall height	6' - 7"	7' - 10"	7' - 11"	8' - 7"
Interior length (approx.)	10' - 0"	14' - 4"	17' - 0"	24' - 0"
Interior width	4' - 9"	5' - 9"	6' - 4"	7' - 8 3/4"
Interior width between wing boxes	-	-	-	6' - 8"
Interior height	4' - 11"	6' - 2"	6' - 2"	6' - 8"
Width of side door	24"	32"	32"	32"
Height of side door	54"	69"	69"	75"
Width of rear door	49 1/2"	61 1/2"	69"	85"
Height of rear door	53"	68"	68"	74"
Height of the floor platform	18 1/2"	19"	19"	23"
Dimension of the hitch	2"	2 5/16"	2 5/16"	2 5/16"
Axle	simple	Tandem with electric brakes	Tandem with electric brakes	Tandem with electric brakes
Tire	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
Wheel	5 nuts	5 nuts	5 nuts	5 nuts
G.A.W.R.	2860 lbs / 1300 kg	3500 lbs / 1588 kg	3500 lbs / 1588 kg	3500 lbs / 1588 kg
G.V.W.R.	2860 lbs / 1300 kg	7000 lbs / 3175 kg	7000 lbs / 3175 kg	7000 lbs / 3175 kg

Specifications are subject to change without notice.



IDEAL CARGO
 IDEALTRAILER.COM
Stand Up to Time!

