

MODEL	# OF UNITS	TIRE/RIM & AXLE CHOICE		GVWR	CARRYING CAPACITY	TRAILER WEIGHT	OVERALL WIDTH	OVERALL LENGTH	HITCH HEIGHT	COUPLER SIZE	AXLE TYPE	BRAKES
		#10384 ST145/R12E ALUM.										
ELITE WCII	2	#07355 20.5X10E #03392 ST175/80D13C #08875 ST145/R12E	#09942 ST175/80D13C ALUM. #10384 ST145/R12E ALUM.	2700	2335	365	101.5	189	16	2	TORSION	N/A
SPECIAL ORDER TRAILERS - CALL YOUR DEALER FOR DETAILS												
ELITE WCIV-SBD	4	#03392 ST175/80D13C #08875 ST145/R12E	#09942 ST175/80D13C ALUM. #10384 ST145/R12E ALUM.	5400	4200	1200	102	343.5	16	2	TORSION	7" Surge Disc 1 Axle Std.

Overall lengths are based on the bunks setup in the farthest position to the rear of the trailer. Hitch height is based on standard tires, upgraded tires will change loaded hitch heights. Prices and specifications may change without notice. Please note: It is the responsibility of the purchaser to adhere to the brake laws regarding trailers. For full information on the laws in your state, contact the appropriate State Motor Vehicle Department. Brake options will change the overall length of trailer. Brake option is Surge Disc Brakes on the Elite WCIV and the WC2-2 trailer. Recommended tongue weight 7-10% of GVWR.